

KUBOTA UTILITY VEHICLE

Kubota

RTV1140CPX



More cargo space or more seating? How about both?

With the new 24.8 HP Kubota RTV1140CPX Four-Seater, you can have both industry-leading cargo capacity and comfortable seating for up to four adults. When hauling cargo is the job, the RTV's standard hydrostatic power steering, heavy-duty VHT Plus transmission and large, hydraulic dumping bed make work easy. When carrying friends, family or coworkers is the task, just reduce the bed size to add a second row of seating. The RTV1140CPX gives you the best of both worlds.

Standard Hydraulic Dumping Bed

Dump sand, gravel, turf, or just about anything you can think of, from the RTV1140CPX's whopping, 0.52 m³/ 0.33 m³ (two-seat and four-seat configurations, respectively) capacity cargo bed. An easy-to-operate lever activates this true hydraulic bed-left system in either two or four-seat configuration.

High Power Diesel Engine

The Kubota D1105 3-cylinder engine, with 1,123cc and 24.8HP, gives the RTV1140CPX excellent acceleration and the ability to take on almost any terrain or task.



VHT Plus (Variable Hydro Transmission)

A Kubota exclusive! The RTV1140CPX's high-performance, three-range VHT Plus offers you the performance you require under demanding conditions. Tackle hills with quick acceleration, smooth, engine-assisted deceleration and superior "hill-holding" abilities. VHT Plus has the power and control to safely take you just about anywhere.





Two-person seating configuration

KUBOTA UTILITY VEHICLE
RTV1140CPX



Four-person seating configuration

KUBOTA UTILITY VEHICLE
RTV1140CPX

An innovative 3-step conversion does the trick.



1 Fold the front and sides of the bed.

The front and front sides of the cargo bed have been built with hinges to conveniently fold up and in towards the back of the bed.

2 Flip down the two-person bench seat and lock it in place.

Next, flip down the hinged bench seat and secure it into place.

3 Slide back the protective screen.

Finally, slide back the protective screen and attached seat back all the way to the bed and lock it in place. Now you're ready to ride. Reverse these three actions for access to the RTV1140CPX's full bed capacity.



Large and Clear Instrumentation

The RTV1140CPX's instrument panel offers a convenient and quick-read layout, so you can spend more time with your eyes on the road. Monitor lamps include oil level, charge status and more.

Hydrostatic Power Steering

Quick, responsive and agile on all terrains. Kubota RTVs were the first vehicle in their class to be equipped with hydrostatic power steering. The RTV1140CPX is no exception.

ROPS Protection

A sturdy standard ROPS (Rollover Protective Structure) and heavy-duty protective screen give you the rollover and accident shelter you and your passengers need.

Specifications

Model		RTV1140CPX	
Engine	Make	KUBOTA D1105-E3-UV	
	Type	3-cylinders, Water cooled 4-cycle, diesel, OHV	
	Displacement	cc	1123
	Horsepower	HP (kW)/rpm	24.8 (18.5)@3000
Fuel tank capacity		ℓ	30
Transmission		Variable hydro transmission (VHT)	
Max. Traveling speed		km/h	40
Wheels, drive system		Rear 2WD or 4WD selection	
Differential lock		Standard; foot operated with mechanical holder	
Gear selection		Hi-Med-Lo range forward, neutral, reverse	
Brakes	Front / Rear	Wet-disc brake	
	Parking brake	Rear wheel, hand lever	
Steering		Hydrostatic power	
Suspension		Independent, Mac-Pherson strut-type / Semi-independent, DeDion axle w/leaf springs and shock absorbers	
Dimensions	Length	mm	3480
	Width	mm	1550
	Height, overall	mm	2000
	Front tread centers	mm	1150
	Rear tread centers	mm	1180
	Wheelbase	mm	2415
	Ground clearance front/rear axle	mm	190 / 190
	Turning radius	m	5.0
Max. rolling weight (Towing capacity)		kg	590
Payload capacity		kg	740
Weight		kg	1075
Cargo bed	Width × Length × Depth	mm	1320×860×290 [2ROWS] / 1320×1360×290 [1ROW]
	Volume	m ³	0.33 [2ROWS] / 0.52 [1ROW]
	Bed height (unloaded)	mm	820
	Cargo bed load	kg	300 [2ROWS] / 500 [1ROW]
Tyres	Front	25×10-12 ATV, 6PLY	
	Rear	25×11-12 ATV, 6PLY	
Front guard		Std.	
Hydraulic bed lift		Std.	
Speedometer		Std.	

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty and safety information. The values in "Ground clearance" and "Weight" are those of the machine equipped with the tires in the table above. Some RTVs in this brochure are shown with optional accessories. For off-highway use only.

KUBOTA (U.K.) LIMITED

Dormer Road Thame, Oxfordshire, OX9 3UN.
 Phone Thame (01844) 214500 Fax (01844) 216685
 E-mail: sales@kubota.co.uk

Web site: <http://www.kubota.co.uk>

RTV

RTV1140

SPECIFICATIONS

Specifications

Model		RTV1140CPX Orange	RTV1140CPX RealTree® Camouflage	
Engine	Make	KUBOTA D1105-E3-UV		
	Type	3-cylinders, Water cooled 4-cycle, diesel, OHV		
	Displacement	cu.in (cc)	68.5 (1123)	
	Horsepower	HP (kW)/rpm	24.8 (18.5)@3000	
Fuel tank capacity	U.S.gals (ℓ)	7.9 (30)		
Transmission		Variable hydro transmission (VHT Plus)		
Max. Traveling speed	mph (km/h)	25 (40)		
Wheels, drive system		4, Rear 2WD or 4WD		
Differential lock		Standard; foot operated with mechanical holder		
Gear selection		Hi-Med-Lo range forward, neutral, reverse		
Brakes	Front / Rear	Wet-disc brake		
	Parking brake	Rear wheel, hand lever		
Steering		Hydrostatic power		
Suspension	Front / Rear	Independent, Mac-Pherson strut-type / Semi-independent, DeDion axle w/leaf springs and shock absorbers		
Dimensions	Length	in. (mm)	137.0 (3480)	
	Width	in. (mm)	61.0 (1550)	
	Height, overall	in. (mm)	78.7 (2000)	
	Front tread centers	in. (mm)	45.3(1150) w/HDWS & ATV, 46.5 (1180) w/Turf	
	Rear tread centers	in. (mm)	46.5(1180) w/HDWS & ATV, 47.6 (1210) w/Turf	
	Wheelbase	in. (mm)	95.1 (2415)	
	Ground clearance front/rear axle	in. (mm)	8.3 (210) / 7.5 (190)	
	Turning diameter	ft. (m)	32.8 (10)	
Max. rolling weight (Towing capacity)	lbs. (kg)	1300 (590)		
Payload capacity	lbs. (kg)	1609 (730)		
Weight	lbs. (kg)	2370 (1075)		
Cargo bed	Width× Length× Depth	in. (mm)	1ROW:52.0(1320)×53.5(1360)×11.4(290) 2ROWS:52.0(1320)×33.9(860)×11.4(290)	
	Volume	cu ft. (m ³)	1ROW:18.7(0.53) 2ROWS:11.7(0.33)	
	Bed height (unloaded)	in. (mm)	33.5 (850)	
	Cargo bed load	lbs. (kg)	1ROW:1102(500) 2ROWS:661(300)	
Tires	Front	25×10-12 HDWS, 6PLY		25×10-12 HDWS, 6PLY
		25×10-12 ATV, 6PLY		25×10-12 ATV, 6PLY
		25×12-12 Turf, 4PLY		—
	Rear	25×10-12 HDWS, 6PLY		25×10-12 HDWS, 6PLY
		25×11-12 ATV, 6PLY		25×11-12 ATV, 6PLY
		25×12-12 Turf, 4PLY		—
Front guard		Std.		
Hydraulic bed lift		Std.		
Speedometer		Std.		

**Realtree® is a registered trademark of Jordan Outdoor Enterprises, Ltd.
The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty and safety information.
The values in "Ground clearance" and "Weight" are those of the machine equipped with the tires. Some RTVs in this web site are shown with optional accessories. For off-highway use only.